



Union Laboratories, Inc., 5600 N. Preston, Flagstaff, AZ 86004 • Phone: (520) 526-8585 • Fax: (520) 526-6778
e-mail: boxer@infomagic.com (Visit Us At www.boxeradhesives.com)

Information sheet for vinyl repair patches (tape)

<u>Temperature Information</u>	<u>Fahrenheit</u>	<u>Celsius</u>
Laminating Temp. (At glue-line)	N/A	N/a
Application Temp. (range)	50 - 150	10 - 65
Maximum Continuous Use	160	71
Intermittent Use	180	82

Surface Preparation

As with all pressure sensitive tapes, it is essential that the surface to which the tape is applied be clean, and free of contaminants such as grease, oil, dust, or algae.

Storage/Shelf Life

One year when stored at 70 degrees F (21 deg. C.)
50% Relative Humidity, out of direct sunlight.

Material Safety Data Sheet

Since Union Laboratories, Inc pressure sensitive tape # 30 and # 10 is neither Toxic nor Hazardous in nature a Material Safety Data Sheet is not required. You may retain this document for your records to satisfy any inquiries you may receive from you customers or local authorities.

PLEASE NOTE: The information given above is based on laboratory test data we believe to be accurate. A 2 mil polyester film is used as support or to cover the side not being tested in most cases. A 30 minute dwell time before testing is standard. Please look upon these values as guides rather than absolutes. Future manufacturing experience may dictate minor changes.

Updated: May 10, 2000