

MATERIAL SAFETY DATA SHEET
FOR COATINGS, RESINS AND RELATED MATERIALS

PAGE #1

DATE OF PREPARATION - 01-01-06

MANUFACTURER'S NAME : Kelley Technical Coatings
ADDRESS : 1445 South 15th Street
ADDRESS : PO Box 3726
ADDRESS :
CITY, STATE : Louisville, Kentucky, 40201-3726

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-
INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 363-9721-

SECTION I -- PRODUCT IDENTIFICATION

MANUFACTURER'S CODE IDENTIFICATION :X1108
PRODUCT CLASS : Aromatic Solvent
TRADE NAME : Rubber Base Solvent
HMIS INFORMATION : HEALTH : 02
FLAMMABILITY : 02
REACTIVITY : 01
PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

SECTION II -- HAZARDOUS INGREDIENTS

----- INGREDIENT -----		%BY	ACGIH	OSHA	SAR NUIS
MATERIAL DESCRIPTION Cas		WEIGHT	T.L.V.	P.E.L	313 PGMT
AROMATIC NAPHTHA					
	64742-95-6	100	100PPM	100PPM	Y N

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

SECTION III -- PHYSICAL DATA

LOWER EXPLOSION LEVEL	1.0 - 1.2	
BOILING RANGE	HIGH 335 DF	LOW 306 DF
VAPOR PRESSURE	3.00 MMHG @ 68DF	
VAPOR DENSITY	HEAVIER THAN AIR	
EVAPORATION RATE	SLOWER THAN BUTYL ACETATE	
WEIGHT PER GALLON	7.29	
% VOLATILE BY VOLUME	100	
% VOLATILE BY WEIGHT	100	
VOC --- LBS/GAL	7.29	LBS/GAL No Water 7.29
GRAMS/LITER	874.8	GRAMS/LITER 874.8

SECTION IV -- FIRE AND EXPLOSION DATA

MANUFACTURER'S CODE X1108

DATE OF PREPARATION - 01-01-06

TRADE NAME Rubber Base Solvent,

FLAMMABILITY CLASSIFICATION OSHA - CLASS II

DOT - COMBUSTIBLE LIQUID UN 1263

LOWEST FLASH POINT T.C.C. 110 DF

LOWER EXPLOSION LEVEL (LEL) 1%

Extinguishing Media: (Yes) - Foam (No) - Alcohol Foam (Yes) - CO2
(Yes) - Dry Chemical (Yes) - Water FogUnusual Fire and Explosion Hazards: - Flammable vapors may form explosive
mixtures with air.Special Fire Fighting Procedures: - Avoid solid stream of water, use fog
for cooling.-----
SECTION V -- HEALTH HAZARD DATA
-----To the best of our knowledge, this product does not
contain any carcinogenic ingredients.Effects of Overexposure: - Liquid may cause eye burns. Prolonged skin
contact with liquid may cause irritation. Eye, nose and throat
irritation may result from exposure to vapor. Narcotic effects occur
at higher concentrations of vapor.

Primary Route(s) of Entry: (X) - Dermal (X) - Inhalation (X) - Ingestion

Emergency and First Aid Procedures:

- Eye contact: Irrigate immediately and thoroughly with water at least
15 minutes and get medical attention.
- Skin contact: Flush immediately and thoroughly with water.
- Inhalation: Remove from exposure, treat symptomatically and get
medical attention.

Medical Conditions Prone to Aggravation by Exposure:

- Pre-existing Respiratory, Eye and Skin Conditions.

SECTION VI -- REACTIVITY DATA

Stability: () - Unstable (X) - Stable

Hazardous Polymerization: () - May Occur (X) - Will Not Occur

Hazardous Decomposition Products: - As with any other organic material,
combustion will produce carbon dioxide and probably carbon monoxide.

Conditions to Avoid: - Not applicable.

Incompatibility (Materials to Avoid): - Oxidizing materials can cause a
vigorous reaction.

MANUFACTURER'S CODE X1108

DATE OF PREPARATION - 01-01-06

TRADE NAME

Rubber Base Solvent,

SECTION VII -- SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Leaked or Spilled:

- Eliminate all ignition sources. Flush spill away with water spray.
- Small spills may be collected with absorbant material.

Waste Disposal Method:

- Mix with a compatible chemical which is less combustible and incinerate.
- Observe all federal, state, and local laws concerning health and pollution.

SECTION VIII -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: - A NIOSH approved respirator for organic vapors should be worn if needed.

Ventilation: - Local exhaust recommended.

- Mechanical (General) recommended.
- Special: None known.

Protective Gloves: - Should be worn.

Eye Protection: - Safety glasses should be worn in any type of industrial operation.

Other Protective Equipment: - Safety shower and eye bath in work area.

Hygienic Practices: - Remove paint from skin contact after exposure.

SECTION IX -- SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: - Material is classified as a flammable liquid. Keep away from heat, sparks and open flame. Keep container closed. Avoid eye contact, prolonged skin contact, and inhalation of high concentrations of vapor. Use with ventilation adequate to maintain vapor concentrations below the TLV of 50 PPM.

Other Precautions: - Hazardous product residue may remain after the product has been removed from its container. Do not reuse "empty" container without commercial cleaning or reconditioning. See also 29 code of federal regulation 1910.1000.